PRODUCT LISTING

Hef-T-Frame[™]

Each Hef-T-Frame[™] Base and Extender is capable of supporting 1,100 lbs. safe working load. Each frame weighs 66 lbs. (Hef-T-Frame[™] Base) and 53 lbs. (Hef-T-Frame[™] Extender).



PH-EF

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
PH-BF	Hef-T-Frame [™] Base	EA	1
PH-EF	Hef-T-Frame [™] Extender	EA	1

Hef-T-Foot[™]

The Hef-T-Foot[™] with strut comes in four lengths – 9.8", 15.7", 23.6", and 39.4". It is manufactured from heavy duty recycled rubber and comes complete with .8" x 1.6" galvanized steel strut adhered to the rubber with industrial adhesive.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
FF-250-S	Hef-T-Foot™ – 9.8" with 1.6" x .8" strut	EA	4
FF-400-S	Hef-T-Foot [™] – 15.7" with 1.6" x .8" strut	EA	4
FF-600-S	Hef-T-Foot [™] – 23.6" with 1.6" x .8" strut	EA	2
FF-1000-S	Hef-T-Foot [™] – 39.4" with 1.6" x .8" strut	EA	1
FF-250-UNI	Hef-T-Foot [™] – 9.8" Universal	EA	4

Hef-T-Foot[™] Installation Variants





About DiversiTech

DiversiTech Corporation is North America's largest manufacturer of equipment pads and a leading manufacturer and supplier of components and related products for the heating, ventilating, air conditioning, and refrigeration (HVACR) industry.

Headquartered in the Atlanta, GA metropolitan area, DiversiTech manufactures a suite of products which includes a wide range of mechanical, electrical, chemical, and structural parts for HVACR and electrical systems, and swimming pool installations. The company maintains manufacturing and distribution facilities in key U.S. locations, Europe, and in the Far East. DiversiTech has enjoyed a continued history of successful growth and has acquired industry-recognized names including Devco® Enterprises, Wagner® Manufacturing, The Black Pad®, Hef-T-Pad™ and Specialty Chemical.

Download an electronic version of this brochure at: www.diversitech.com/literature/lit-fly-foot.pdf

DiversiTech Corporation 6650 Sugarloaf Parkway Duluth, GA 30097 800.995.2222 678.542.3700 FAX www.diversitech.com

©2011 DiversiTech Corporation LIT-FLY-FOOT, 1/11



HEF-T SUPPORT SYSTEMS

HEF-T-FRAME[™] and HEF-T-FOOT[™] Equipment Support Systems

HEF-T-FRAME[™]

The flexibility of the Hef-T-Frame[™] makes "designing" simple. The design consists of a Hef-T-Frame[™] Base and a Hef-T-Frame[™] Extender which combine to provide a solution for mounting any type of equipment.

Simply start with a Hef-T-Frame[™] Base and add the required number of Hef-T-Frame[™] Extenders to create your own system. Hef-T-Frame[™] Extenders can be added in any direction to make a system of any size in multiples of 4'. Each frame has a maximum dimension of 4'.

Each Hef-T-Frame[™] Base and Extender is capable of supporting 1,100 lbs. safe working load. Be sure the underlying roof structure can support the weight of the equipment and frame system. Each frame weighs 66 lbs. (Hef-T-Frame[™] Base) and 53 lbs. (Hef-T-Frame[™] Extender).





HEF-T-FRAME[™] Installation



The Hef-T-Foot[™] is used to support small pipework, runs of cable tray, or as an alternative for supporting condensing units, air source heat pumps or a variety of outdoor equipment.

The Hef-T-Foot[™] with strut comes in

four lengths -9.8", 15.7", 23.6", and 39.4". It is manufactured from heavy duty recycled rubber and comes complete with .8" x 1.6" galvanized steel strut adhered to the rubber with industrial adhesive. The rubber is strong and durable with drain slots moulded into the underside to allow standing water to flow under the foot.



HEF-T-FOOT™ Rooftop/ Ground Mount Installation

HEF-T-FOOT" Utility Room Installation, Gravity Drain



HEF-T-FOOT™ Rooftop/Ground Mount Accessory/Pipe Support Installation

Step 2









Condensate management is needed for heat pumps,