

Pro-Lube ALK 200

Alkylbenzene

Refrigeration Compression Oil

200 SUS Viscosity at 100 °F

OEM-Approved*

WARNING! May be harmful if
swallowed and enters airways.
Causes mild skin and eye irritation.



1 U.S. Gallon (3.78 Liters)

DESCRIPTION: Alkylbenzene Series Refrigeration Oils are recommended for refrigeration, air conditioning and heat pump applications using HCFC and CFC refrigerants. This series is an excellent choice when retrofitting to the new refrigerants which are HCFC based such as R-401A (MP-39), R-401B (MP-66), R-402A (HP-80), R-402B (HP-81). When retrofitting a compressor to a new refrigerant, always follow the OEM's recommendation. The Alkylbenzene series is specially filtered to meet its high standard of purity.

ALKYLBENZENE REFRIGERATION OIL RECOMMENDATION CHART

CURRENT REFRIGERANT	R-12, R-502	R-11	R-12 R-114	R-12	R-500	R-502
REPLACEMENT REFRIGERANT	R-22	R-123	R-124	R-401A (MP-39) R-401B (MP-66)	R-401B (MP-66)	R-402A (HP-80) R-402B (HP-81) R-403B (Is c-6 9L)
RECOMMENDED LUBRICANT	ALKYL 150 ALKYL 300	ALKYL 150 ALKYL 300	ALKYL 150 ALKYL 300	ALKYL 150 ALKYL 200ca ALKYL 300	ALKYL 150 ALKYL 200ca ALKYL 300	ALKYL 150 ALKYL 200ca ALKYL 300

WARNING! May be harmful if swallowed and enters airways. Causes mild skin and eye irritation. Keep out of reach of children. Read label before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapours, or spray. Do not get in eyes, on skin, or on clothing. Wear protective gloves, clothing, eye protection, and face protection.

FIRST AID: IF SWALLOWED: If more than several ounces of material are swallowed, DO NOT induce vomiting. Give two 16 ounce glasses of water and get medical attention or call the nearest poison control center for advice. **IF ON SKIN:** Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the affected person should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds. **IF INHALED:** Evacuate to a safe area with plenty of fresh air. Allow the affected individual to rest in a well ventilated area. Seek medical aid if breathing does not return to normal within 15 minutes. **IF IN EYES:** Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

IN CASE OF FIRE: Use any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray or firefighting foam. See Safety Data Sheet for further details regarding safe use of this product.

NON-WARRANTY: This product is provided "as is". Seller specifically disclaims any and all warranties, whether expressed, implied, statutory or otherwise and specifically disclaims all implied warranties including without limitation, any implied warranties of merchantability or fitness for a particular purpose or those arising by reason of custom or usage in the trade or by course of dealing.

MADE IN USA
DOC13613

***Made from OEM-Approved feedstocks**

Packaged & Distributed by:
DiversiTech Corporation
6650 Sugarloaf Parkway
Duluth, GA 30097 **678.542.3600**

Manufactured By:
SOLTEX
3707 FM 1960 West
Suite 560
Houston, TX 77068



8

95247 09035

0