

Product Family

PVC Condensate Pipe

Description

These pipes are designed to meet most all residential, industrial and irrigation/agricultural needs. Smooth inner walls allow for low pressure drops and resistance to chemicals and corrosion.



5-2001

Specifications

Material:

PVC

Type:

Schedule 40

Warranty:

1 year

STOCK NO	Description	Length	Maximum Temperature	Maximum PSI	Material	Weight	UPC
5-2001	1/2in. PVC – PSI 315 – 10ft. Straight End	10 feet	140°F	358 PSI	PVC	0.09 lbs	0095247108480
5-2002	3/4in. PVC – PSI 200 – 10ft. Straight End	10 feet	140°F	289 PSI	PVC	0.14 lbs	0095247124343
5-2005	3/4in. PVC – PSI 200 – 20ft. Belled End	20 feet	140°F	289 PSI	PVC	0.131 lbs	0095247003068
5-401	3/4in. PVC – Sch. 40 – 10ft. Straight End	10 feet	140°F	289 PSI	PVC	0.224 lbs	0095247003136
5-404	2in. PVC – Sch.40/DWV, ASTM 2665 – 10ft. Straight End	10 feet	140°F	166 PSI	PVC	0.695 lbs	0095247072736
5-405	3in. PVC – Sch.40/DWV, ASTM 2665 – 10ft. Straight End	10 feet	140°F	158 PSI	PVC	1.435 lbs	0095247072767
5-407	3/4in. PVC – Sch. 40 – 20ft. Belled End	20 feet	140°F	289 PSI	PVC	0.218 lbs	0095247003174
5-416	1in. PVC – Sch. 40 – 20ft. Belled End	20 feet	140°F	270 PSI	PVC	0.5 lbs	0095247108497
5-417	1-1/4in. PVC – Sch. 40 – 20ft. Belled End	20 feet	140°F	221 PSI	PVC	0.5 lbs	0095247108503
5-418	1-1/2in. PVC – Sch. 40 – 20ft. Belled End	20 feet	140°F	198 PSI	PVC	0.5 lbs	0095247108510



Simplify The Way You Work

6650 Sugarloaf Parkway, Duluth, GA 30097 Phone: 800-955-2222 Fax: 678-542-3700 www.diversitech.com

© 2016 Diversitech Corporation

All rights reserved.

Rev. 4/11/17

Page 1 of 1