

Motor Run Capacitors

Product 4J Motor Run Capacitor Series

Purpose The DiversiTech Motor Run Capacitors are guaranteed for 10,000 hours of life under normal operating conditions. They have an operating life of 94% at 60,000 hours. They are dual capacitance, and designed for continuous run.

- Features**
- Quick connect terminals
 - Oval metal housing
 - Applied Standard: UL-810; CSA22.2 No190, IEC60252
 - Meets 10,000 AFC safety requirement per UL-810
 - Oil Filled; Non PCB

- General Specifications**
- UL Recognized
 - Connection Size: 0.250 in
 - Connection Type: Tab
 - Permissible Temperature: -40°C to +70°C
 - Capacitance Tolerance +/-5%
 - Withstanding Voltage test Between Terminals: Rated Voltage X 1.75VAC, 10sec Between Terminals and Case: Rated Voltage X 2+1000VAC, 60sec
 - Maximum Permissible Voltage: 110% of the rated voltage
 - Maximum Permissible Current: 130% of the rated current

- Dimensions**
- 4JJ0545: H = 6.75in, L = 3.0in, W = 2.0in
 - 4JJ0555: H = 4.75in, L = 3.75in, W = 2.0in
 - 4JJ0560: H = 6.25in, L = 4.5in, W = 4.5in
 - 4JJ7545: H = 6.5in, L = 3.0in, W = 2.0in

General Characteristics

Anchor Model	Voltage	Frequency	Capacitance	Weight
4JJ0545	440 VAC	50-60 Hz	45+5 μ F	1.0 lbs
4JJ0555	440 VAC	50-60 Hz	55+5 μ F	0.962 lbs
4JJ0560	440 VAC	50-60 Hz	60+5 μ F	1.0 lbs
4JJ7545	440 VAC	50-60 Hz	45+7.5 μ F	0.8 lbs



Dissipation Chart	
Capacitor Value Range	Dissipation Factor Max.
up to 7.5 μ F	0.25%
7.6 μ F to 15 μ F	0.25%
16 μ F to 25 μ F	0.30%
26 μ F to 40 μ F	0.45%
41 μ F to 70 μ F	0.70%

