

CS-1

Product Condensate Tee Switch

Purpose DiversiTech Flood Prevention Switches are simple to install, easy to service, and extremely reliable. As water level in the auxiliary or main drain pipe rises due to a clogged air conditioning condensate drain, the switch shuts off the system, thus preventing water from overflowing and causing damage to doors, walls, and ceilings.

- Features**
- Small size for serviceability
 - Has a pull-to-test lever for verifying correct installation
 - Constructed of materials that will not rust or stick
 - Switch operates smoothly every time
 - Intergrated LED light indicator notifies homeowners and technicians activation has occurred
 - Internal surge protector eliminating the risk of inadvertent shutdowns
 - Can be configured to be used with drain pans or in-line with drain lines
 - Comes with 6 feet of wire for easy installation

- General Specifications**
- Voltage: 24 volts
 - Amperage: 1.5 amps
 - Operates via a reed switch
 - ETL Listed
 - Conforms to UL 508

General Characteristics

Part Number	Type	Switch Type	Order Multiple
CS-1	Tee	Magnetic Reed	10

- | | |
|---|---|
| 1 | Sensor Assembly
Sistema del sensor |
| 2 | Pipe Tee
Punto de salida de la tubería |
| 3 | 1" x 3/4" Bushing
Casquillo 1" x 3/4" |
| 4 | PVC Cap
Tapa de PVC |
| 5 | 3/4" Threaded Fitting
Accesorios de rosca 3/4" |



Intertek

5010060