

SDS# ATK-1P  
Date: January 2016

Total Pages: 5

# Acid Test Kit

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Acid Test Kit for Poly Ester Oil  
**Catalog Number:** ATK-1P  
**Manufactured by:** DiversiTech Corporation  
6650 Sugarloaf Parkway  
Duluth, GA, 30097  
**Information Phone No.:** 1+678.542.3600  
**EMERGENCY Phone No.:** 1 800.255.3924 Chem-Tel (Chemical Emergencies)  
**PREPARED BY:** V. Leone

## SECTION 2. HAZARDOUS IDENTIFICATION

### GHS Classification:

Flammable Liquids Category 2  
Acute Toxicity Oral Category 4  
Acute Toxicity inhalation Category 4  
Acute Toxicity Dermal Category 4  
Skin Irritation Category 2  
Eye Irritation Category 2A  
Specific Target Organ Toxicity- Single Exposure Category 2

### Label Elements:



**Signal Word:** Danger!

### Hazard Statement(s)

H225 Highly flammable liquid and vapor  
H302 Harmful if swallowed  
H312 Harmful in contact with skin  
H332 Harmful if inhaled  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H371 May cause damage to organs, eyes, skin, respiratory system, central nervous system.

### Precautionary statement(s)

P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat, sparks, open flames, or hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe mist or vapors.  
P264 Wash thoroughly after handling.  
P270 Do not eat, drink, or smoke when using this product.  
P271 Use only outdoors or in a well ventilated area.  
P280 Wear rubber, nitrile or neoprene protective gloves and clothing, and safety goggles or face shield to protect eyes and face.

# Acid Test Kit

## SECTION 2. HAZARDOUS IDENTIFICATION (cont.)

P303 + 361 + 353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P332+313	If skin irritation occurs: Get medical attention.
P362 + 364	Take off contaminated clothing and wash it before reuse.
P301+312	IF SWALLOWED: Call a poison control center or doctor if you feel unwell.
P330	Rinse mouth.
P304+340	If INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a Poison Center or doctor if you feel unwell.
P305 + 351 + 338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + 313	If eye irritation persists: Get medical attention.
P370+378	IN CASE OF FIRE: Use foam or Carbon dioxide extinguishing media to extinguish.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents to appropriate facility in accordance with Federal, State, and local regulations.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS No.	EINECS No.	% or Range	GHS Classification
Isopropanol	67-63-0	200-661-7	45-55*	H225: Highly flammable Liquid and vapor. H319: Causes serious Eye irritation. H336: May cause Drowsiness or dizziness H225: Highly flammable Liquid. H301: Acute Toxic. H311: Toxic if in Contact with skin. H331: Toxic if inhaled H370: Causes damage To organs.
Methanol	67-56-1		45-55*	Category 2 Category 2A Category 3 Category 2 Category 3 Category Category

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## SECTION 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

**Ingestion:** DO NOT INDUCE VOMITING! Give large quantities of water or milk if available. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Skin Contact:** Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician, immediately. Wash clothing before reuse.

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

### 4.2. Signs and Symptoms of Exposure:

**Inhalation:** High vapor concentration may cause burning sensation in nose and throat and stinging and watering in the eyes. At concentrations which cause irritation, dizziness, faintness, drowsiness, nausea and vomiting may also occur.

**Ingestion:** May cause dizziness, faintness, drowsiness decreased awareness or responsiveness, nausea, vomiting, staggering gait, lack of coordination, blindness, coma and death.

**Skin Contact:** Prolonged or repeated contact may cause defatting and drying of the skin.

**Eye Contact:** May cause irritation including stinging, tearing, and redness.

Effects of Repeated Overexposure: Long term repeated oral exposure to ethanol may result in the development of progressive liver injury with fibrosis.

Overexposure to methanol may cause eye damage and liver or kidney injury.

# Acid Test Kit

## SECTION 5. FIREFIGHTING MEASURES

### Suitable and Unsuitable Extinguishing Media:

Apply alcohol-type or all-purpose foam by manufacturer's recommended techniques for large fires. Use carbon dioxide or dry chemical media for small fires.

### Special Equipment and Precautions for Fire –Fighters:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face-piece operated in the pressure demand or other positive pressure mode. Use water spray to cool fire-exposed containers and structures; Use water spray to disperse vapors - re-ignition is possible. Vapors may travel to source of ignition and flash back. Vapors may settle in low or confined spaces, or produce a floating fire hazard. Static ignition hazard can result from handling and use.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions, Protective Equipment and Emergency Procedures:** Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment and clothing during clean-up.

**Methods and Material for Containment and Clean-Up:** Small spills can be wiped or soaked up. Large spills: Eliminate all ignition sources; ground all equipment; do not walk through spill; stop spill if possible; prevent entry into sewers, confined spaces, etc.; use a vapor suppressing foam to reduce vapors; absorb spill with noncombustible matter and transfer to containers; use non-sparking tools to collect absorbed material. Refer to section 11 for disposal information.

## SECTION 7. HANDLING AND STORAGE

**Precautions for Safe Handling:** Keep in a tightly closed container. Protect from physical damage. Keep this and all chemicals out of the reach of children. Wash thoroughly after handling.

**Conditions for Safe Storage, Including any Incompatibilities: Store locked up.** Store in a well-ventilated place. Keep cool. Flammable material - keep away from heat, sparks, and flame; sudden releases of hot organic vapors or mists from process equipment operating at elevated temperature may result in ignitions without the presence of obvious ignition sources. Observe all warnings and precautions listed for the product.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Airborne Exposure Limits:

**Isopropanol** (CAS# 67-63-0) 400 ppm TWA (OSHA) 980mg/m<sup>3</sup> TWA (OSHA) 2000ppm IDLH (NIOSH)

**Methanol** (CAS# 67-63-0) 200 ppm TWA 260mg/m<sup>3</sup>

### Appropriate Engineering Controls:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, [\*Industrial Ventilation. A Manual of Recommended Practices\*](#), most recent edition, for details.

### Personal Respirators (NIOSH Approved):

Use in a well-ventilated area. If vapors are generated and exceed the TLV, use of air-purifying respirators and follow respiratory program meeting OSHA 910.134 and ANSI Z88.2 requirements.

**Skin Protection:** Wear rubber, neoprene, nitrile, Saranex® boots, gloves, lab coat, apron or coveralls, as necessary and appropriate, to prevent skin contact.

**Eye Protection:** Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities or a source of running water in the work area.

**Work Hygienic Practices:** Use proper industrial hygiene practices to minimize hazardous exposure. Wash hands after handling this material, and before eating, smoking or using the bathroom.

# Acid Test Kit

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Maroon/purplish liquid  
**Odor:** alcohol-like  
**Odor Threshold:** Not established  
**pH @ 25°C:** Not available  
**Melting Point (Pour Point):** Not available  
**Boiling Point:** 82°C @ 760 mmHg  
**Flash Point:** 12°C (54°F)  
**Evaporation Rate (Water = 1):** 1.7 (n-butyl acetate=1)  
**Flammable Limits:**  
LEL: 2.0 °C  
UEL: 12.7°C  
**Vapor pressure (mm Hg):** 33 mm Hg @ 20°C  
**Vapor Density (Air = 1):** 2.1

**Specific gravity (H2O = 1):** 0.85  
**Solubility in water:** Miscible  
**Octanol/Water Partition Coefficient:** Not available  
**Autoignition Temperature:** 399 °C ( 750 ° F)  
**Decomposition Temperature:** Not available

## SECTION 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable under ordinary conditions of use and storage.  
**Possibility of Hazardous Reactions:** Will not occur.  
**Conditions to Avoid:** Extreme heat, incompatibles.  
**Incompatible Materials:** Strong oxidizers and strong acids  
**Hazardous Decomposition Products:** May evolve carbon monoxide, carbon dioxide if burned.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Potential Health Effects:

**Inhalation: Harmful if inhaled.** High vapor concentration may cause burning sensation in nose and throat and stinging and watering in the eyes. At concentrations which cause irritation, dizziness, faintness, drowsiness, nausea and vomiting may also occur.  
**Ingestion: Harmful if swallowed.** May cause dizziness, faintness, drowsiness decreased awareness or responsiveness, nausea, vomiting, staggering gait, lack of coordination, blindness, coma and death.  
**Skin Contact: Harmful in contact with skin.** Prolonged or repeated contact may cause defatting and drying of the skin  
**Eye Contact:** May cause irritation including stinging, tearing, and redness.  
**Effects of Repeated Overexposure:** Long term repeated oral exposure to Methanol may result in the development of progressive liver injury with fibrosis. Overexposure to methanol may cause eye damage and liver or kidney injury.  
**Carcinogenic effects:** Methanol - Not listed by ACGIH, IARC, or NTP.  
**Teratogenicity/Reproductive toxicity: No data available.**

**Mutagenic effects:** No information available

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity: Isopropanol: Fish:** Fathead Minnow: >1000 ppm; 96h; LC50  
Daphnia: >1000 ppm; 96h; LC50  
Gold orfe: 8970-9280 ppm; 48h; LC50

**Aquatic:** IPA as a high biochemical oxygen demand and a potential to cause oxygen depletion in aqueous systems, a low potential to affect aquatic organisms, a low potential to affect secondary waste treatment microbial metabolism, a low potential to affect the germination of some plants, a high potential to biodegrade (low persistence) with unacclimated microorganisms from activated sludge.

**Persistence and Degradability:** biodegradable

**Bioaccumulative Potential:** No data available

**Mobility in Soil:** From soil, substance evaporates and is microbially biodegraded

**Other Adverse Effects:** None known

**Other:** For more information, see "HANDBOOK OF ENVIRONMENTAL FATE AND EXPOSURE DATA."

# Acid Test Kit

## SECTION 13. DISPOSAL CONSIDERATIONS

Vapors may collect in empty containers. Treat empty containers as hazardous.  
Dispose of spill-clean up and other wastes in accordance with Federal, State, and local regulations

## SECTION 14. TRANSPORTATION INFORMATION

**US DOT:** UN1993, Flammable liquid, N.O.S. (Contains methanol and isopropanol), 3, PGII  
**UN ID #:** 1993  
**Proper Shipping Name:** Flammable liquid, N.O.S. (Contains methanol and isopropanol)  
**Packing Group:** II  
**UN Number:** None  
**UN Proper Shipping Name:** Flammable Liquid, N.O.S. (Contains methanol and isopropanol)  
**Transport Hazard Class(s):** 3  
**Packing group:** None  
**Environmental Hazards:** Not a marine pollutant  
**ADR/RID Transport Information ADR/RID Class:** 3  
**ADR/RID Packing Group:** II  
**IMDG Hazard Class:** 3  
**IMDG Packing Group:** II  
**ADNR Class:** 3  
**ADNR Item:** UN1993  
**IATA Hazard Class:** 3  
**ATA Packing Group:** II  
**Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable  
**EmS:** F-E / S-D

## SECTION 15. REGULATORY INFORMATION

**US EPA**  
**Comprehensive Environmental Response Compensation and Liability**

**Act of 1980 (CERCLA)** requires notification of the National Response Center of release quantities of Hazardous Substances is not required for this material.

### WHMIS:

This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

## SECTION 16. OTHER INFORMATION

**Revision Summary:** All Sections: New GHS Format  
**SDS DATE REVISED:** 01/05/2016

HMIS III Ratings:  
**HMIS III®**

Health	1
Flamability	3
Physical Hazard	0
Personal Protection	B

*This information is, to the best of our knowledge and belief, accurate and reliable as of the date completed. However no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the completeness and suitability of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information, nor do we offer any warranty against patent infringement.*