

Pro-Prime PVC Primer

MSDS# PP

May 2012

5 Total Pages

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Pro-Prime PVC Primer

Manufactured by: Diversitech

6650 Sugarloaf Parkway, Duluth, GA 30097

Phone: 800-995-2222 (Product Information)

Phone: 800-255-3924 (CHEM-TEL, Chemical Emergencies Only)

Date: 05/31/2012

Prepared By: Wyatt Coleman

2. HAZARDS IDENTIFICATION

Emergency Overview: Clear - cloudy liquid with ether-like odor. Extremely flammable liquid and vapors. May cause irritation to skin, eye, respiratory tract and other mucous membranes.

Potential Health Effects: Routes of exposure include; inhalation, skin absorption, skin contact, eye contact and ingestion.

Eyes: Can cause irritation and permanent eye injury. Symptoms include stinging, tearing, redness and swelling of eyes.

Skin: May cause mild skin irritation. Prolonged or repeated contact may dry the skin and cause dermatitis. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

Ingestion: If ingestion occurs seek medical attention immediately. May cause irritation of nose, throat and can lead to liver and kidney damage. May be fatal if swallowed.

Inhalation: May cause irritation to the nose, throat, mucous membranes and other tissues of the respiratory system. Symptoms include dizziness, drowsiness, fatigue, headache, nausea, coughing and shortness of breath. Overexposure may cause liver and kidney damage.

HEALTH HAZARDS: Acute: Over exposure to this product can be irritating to the eyes, skin and mucous membranes, and can also cause central-nervous system effects (dizziness, nausea and headaches). Ingestion of this product, or inhalation of high concentrations of this product's vapors, may be fatal.

Chronic: Prolonged or repeated skin exposures can lead to dermatitis. May cause conjunctivitis with prolonged or repeated eye exposure. May cause liver, kidney and reproductive damage.

Medical Conditions Aggravated by Exposure: Pre-existing disorders of the following organs may be aggravated by exposure to this material: skin, lung, liver, kidney.

3. COMPOSITION / INFORMATION INGREDIENTS

Hazardous Ingredients	CAS Number	ACGIH		OSHA	
		TLV ppm	STEL ppm	PEL ppm	STEL ppm
Tetrahydrofuran	109-99-9	50, skin	100	200	250
Cyclohexanone	108-94-1	20, skin	50	25	
Methyl Ethyl Ketone	78-93-3	200	300	200	300
Acetone	67-64-1	500	750	750	1000

Pro-Prime PVC Primer

4. FIRST-AID MEASURES

Eyes: Immediately move individual away from exposure into fresh air. Flush eye gently with water for at least 15 minutes while holding eyelids apart. Seek immediate medical attention.

Skin: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center. Do not induce vomiting.

Inhalation: Move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen; seek medical attention immediately.

5. FIREFIGHTING MEASURES

Fire Extinguishing Media: Use foam, carbon dioxide (CO₂), dry chemical.

Special Fire Fighting Procedures: Incipient fire responders should wear eye protection. Firefighters must wear self-contained breathing apparatus and full protective equipment.

Unusual Fire and Explosion Hazards: Class IB Flammable Liquid. Keep away from sources of heat, sparks or flame. If ignited, may form carbon dioxide and carbon monoxide, various hydrocarbon vapors and toxic gases. Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak: Eliminate all ignition sources (flares, flames including pilot lights electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean metal containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal in accordance with U.S. Federal, State, or local procedures.

7. HANDLING AND STORAGE

Handling and Storage Precautions : Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames. If transferring this material to other containers, ground all containers to avoid static electricity buildup and discharge which may ignite flammable vapors.

Other Precautions: Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, solid) all hazard precautions given in the data sheet must be observed. Avoid prolonged or repeated contact with skin or clothing.

8. EXPOSURE CONTROLS /PERSONAL PROTECTION

Respiratory Protection: In confined or poorly ventilated areas, use NIOSH/MSHA approved air respirators. Use only protection authorized in 29 CFR 1910.134 or applicable State regulations.

Eye Protection: Splash goggles or safety glasses.

Hand Protection: Wear rubber gloves

Other Protection: Wear protective clothing appropriate for task (coveralls, apron, Tyvek suit)

Specific Engineering Controls (such as ventilation, enclosed process): Use in well ventilated area. Provide ventilation capable of maintaining emissions at the point of use below recommended exposure limits. Mechanical exhaust (explosion proof) may be required. Emergency eye-wash / safety showers are needed where there is the possibility that an employee's eyes may be exposed to this material, the employer should provide an eye-wash fountain / safety shower within the work area for emergency use.

Pro-Prime PVC Primer

9. PHYSICAL AND CHEMICAL CHARACTERISTICS

Appearance: Various (clear, purple), liquid

Odor: Ether-like

Odor threshold: No data for mixture

pH: No data for mixture

Melting Point: No data for mixture

Boiling Point: 151°F / 66°C

Flash Point (Method Used): 6°F / -14°C

Evaporation Rate (Ether = 1): 8.0

Flammability (Solid, gas): Class IB Flammable Liquid

Upper/lower flammability or explosive limits: 12.8% / 1.8%

Vapor pressure (mm Hg): 143 mm Hg @ 20°C

Vapor Density (Air=1): 2.5

Specific gravity (H₂O = 1): 0.91

VOC Content: Maximum VOC emissions when applied and tested per SCAQMD Rule 1168, Test Method 316A is 510

Grams/Liter (g/l)

% Volatile by Weight: 100%

Solubility in water: Negligible

Partition coefficient: No data for mixture

Auto-ignition temperature: No data for mixture

Decomposition temperature: No data for mixture

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur.

Incompatibility (Materials to Avoid): Oxidizers, acids and bases.

Reactive Conditions to avoid: Avoid heat, sparks, flames and other sources of ignition.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, hydrogen chloride and other various hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Sensitization: None of the components of this product are known to cause sensitization.

Suspected Cancer Agent: None of the components of this product are listed as an IARC, NTP or OSHA carcinogen.

Tetrahydrofuran – The National Toxicology Program has reported that exposures of mice and rats to THF vapor levels up to 1800 ppm 6 hr/day, 5 days/week for their lifetime caused an incidence of kidney tumors in male rats and liver tumors in female mice. The significance of these findings for human health are unclear at this time, and may be related to “species specific” effects. Elevated incidences of tumors in humans have not been reported for THF. ACGIH has classified Cyclohexanone and Tetrahydrofuran as “A3”, Confirmed Animal Carcinogens with Unknown Relevance to Humans.

Reproductive Toxicity: This product is not reported to produce reproductive effects in humans. Reproductive toxicity data is available for Acetone, Methyl Ethyl Ketone, Cyclohexanone and Tetrahydrofuran; obtained through clinical studies on test animals exposed to relatively high doses.

Mutagenicity: This product is not reported to produce mutagenic effects in humans. Human mutation data is available for Cyclohexanone; obtained through clinical studies on specific human tissues exposed to relatively high doses. Animal mutation data is available for Acetone, Methyl Ethyl Ketone and Tetrahydrofuran; obtained through clinical studies on specific animal tissues or micro-organisms exposed to relatively high doses.

Pro-Prime PVC Primer

Medical Conditions Aggravated By Exposure: Pre-existing disorders of the following organs may be aggravated by exposure to this material: skin, lung, liver, kidney.

Tetrahydrofuran:	Oral rat LD50: 1,650 mg/kg Inhalation rat LC50: 21,000 ppm / 3 hours
Cyclohexanone:	Oral rat LD50: 1,620 mg/kg Skin rabbit LD50: 1 mL/kg Inhalation rat LC50: 8,000 ppm / 4 hours
Methyl Ethyl Ketone:	Oral rat LD50: 2,737 mg/kg Skin rabbit LD50: 6,480 mg/kg Inhalation rat LC50: 23,500 mg/m3 / 8 hours
Acetone:	Oral rat LD50: 5,800 mg/kg Inhalation rat LC50: 50,100 mg/m3 / 8 hours

12. ECOLOGICAL INFORMATION

This product is not expected to be toxic to aquatic organisms.

Tetrahydrofuran:	96 hour LC50 fathead minnow: 2160 mg/l
Cyclohexanone:	96 hour LC50 values for fish is over 100 mg/l
Methyl Ethyl Ketone:	96 hour LC50 values for fish is over 100 mg/l
Acetone:	96 hour LC50 values for fish is over 100 mg/l

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose in accordance with current local, state and federal regulations.

14. TRANSPORT INFORMATION

	Proper Shipping Name		UN Number		Hazard Class /Packing Group		Label	
	Less than 1 Liter	Greater than 1 Liter	< 1 Liter	> 1 Liter	< 1 Liter	> 1 Liter	< 1 Liter	> 1 Liter
DOT	Consumer Commodity	Flammable liquids, n.o.s.	None	UN 1993	ORM-D	3, PG II	None	Flammable Liquid
IMDG	Flammable liquids, n.o.s.		UN 1993		3, PG II		None (Limited Quantity)	Flammable Liquid

15. REGULATORY INFORMATION

SARA Reporting Requirements:	CHEMICAL NAME	SARA 302 (40 CFR 355, Appendix A)	SARA 313 (40 CFR 372.65)
This product contains the following chemicals subject to Sections 302 and 313 of Title III of the Superfund Amendments and Reauthorization Act:	Tetrahydrofuran	No	No
	Cyclohexanone	No	No
	Methyl Ethyl Ketone	No	Yes
	Acetone	No	No
U.S. CERCLA Reportable Quantity: Tetrahydrofuran = 1000 lbs.; Cyclohexanone = 5000 lbs.; Methyl Ethyl Ketone = 5000 lbs.; Acetone = 500 lbs.			

Pro-Prime PVC Primer

<p>California Proposition 65: This product may contain trace levels of chemicals known to the State of California to cause cancer. Exposure to these chemicals above the State of California 'No Significant Risk Level' is unlikely under normal use conditions.</p>
<p>TSCA Inventory: The components of this product are listed on the TSCA Inventory.</p>
<p>Canadian WHIMS Classification: Class B2: Flammable Liquid; Class D2A/B: Materials Causing Other Toxic Effects</p>

16. OTHER INFORMATION

NFPA and HMIS:

NFPA Hazard Signal: Health: 2 Flammability: 3 Reactivity: 1 Special: None
 HMIS Hazard Signal: Health: 2 Flammability: 3 Reactivity: 1 PPE: G

This information is, to the best of our knowledge and belief, accurate and reliable as of the date completed. However no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the completeness and suitability of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information, nor do we offer any warranty against patent infringement