

## Pan Patch

**Product** Pan Patch

- Features**
- 2 part epoxy creates permanent bond
  - Stops leaks or holes in drain pans
  - Fast acting formula
  - Long lasting results
  - Works through standing water
  - Self-leveling formula
  - Shelf life: 2 years

- Benefits**
- Repairs pan leaks to save replacement cost
  - Takes only minutes to apply
  - Permanent bond stops leaks to prevent damage
  - Provides smooth, even coat to ensure proper application

**Application** Pan-Patch™ is a unique two-part epoxy that adheres to almost any surface, including metal, wood and concrete. It pours through standing water to create a permanent bond. And it also includes an anti-microbial additive to eliminate future mold growth. Pan-Patch has a self-leveling formula that will provide a smooth, even coat.

- Directions**
1. Remove large loose particles from pan.
  2. Neutralize oils and acids prior to an application.
  3. Create a downhill angle and pour material directly into the pan for self leveling or for larger pans apply with a brush or adhesive roller.
  4. Pour contents of Part B (hardener) into Part A (base).
  5. Mix thoroughly until contents are the same color and texture.
  6. Apply to surface.
- Note: Failure to mix thoroughly could result in poor adhesion to surface.



### General Characteristics

Model	Description	UPC	Order Multiple
PANPATCH	1 gallon, 160 sq. ft.	0095247141784	4
PANPATCH-32	1 quart, 40 sq. ft.	0095247141777	9
PANPATCH-BAG	bag, 8 sq. ft.	0095247141760	10