

Specifications

Product Pro-Lube-ALK™ 150 Synthetic Refrigeration Compressor Oil

Application Air conditioning and refrigeration compressors.

Purpose Pro-Lube-ALK™ 150 is an ISO 32 synthetic aromatic hydro-carbon lubricant formulated from alkylbenzene refrigerant oil designed for use in refrigeration compressors.

Advantages Pro-Lube-ALK™ 150 is extremely stable and compatible with refrigerant gases, except R-134a, system components and mineral oil compressor lubricants. Its oil return properties are superior to mineral oil refrigeration lubricants. Pro-Lube-ALK™ 150 is compounded from OEM-Approved stocks. Pro-Lube-ALK™ 150 is a high purity refrigeration oil with excellent lubricating and wear protection properties. It eliminates heat transfer surface fouling, evaporator and expansion valve plugging, sludge formation and lubricant degradation that may occur in systems using conventional mineral oils. Pro-Lube-ALK™ 150 has superior high and low temperature service properties in most CFC and HCFC refrigerants. Pro-Lube-ALK™ 150 has a long service life. It is suitable for use in Reciprocating-Semi-hermetic, Rotary, Scroll, Centrifugal and Screw type industrial and domestic air conditioning compressors.

Product Properties


- Kinematic Viscosity @ 40°C (cSt): 29-35
- Floc Point (°C): -65
- Pour Point (°C): -45
- Closed Flash Point (°C): 150
- Dielectric KV: 30
- Specific gravity: 0.86
- Total acid number (mg KOH/g): 0.02

Safety Data Consult the Material Safety Data Sheet before using this product. Do not use this product until you have read all warning statements on the label and have consulted the MSDS. This product is only to be used by trained professional personnel. Use Pro-Lube-ALK™ 150 only according to label directions. Wash thoroughly after using this product.

Caution: Avoid eye and skin contact. Avoid vapor. Do not take internally.

First Aid: In case of eye contact, flush the affected area with water for 15 minutes. If irritation persists, get medical attention. For skin contact, wash thoroughly with soap and water. For ingestion, immediately drink 3-4 glasses of water. Do not induce vomiting. Get medical attention. For inhalation, remove the individual to fresh air if irritation occurs. If breathing does not return to normal within a few minutes, get medical attention.

Keep out of reach of children.



Package Metrics

Producer of Goods Specialty Chemical Manufacturing, A DiversiTech Company

Domestic/Foreign Commodity Domestic

SKU Specific Package Metrics

Catalog No.	Description	Size	UPC	Quantity per Case
ALK150-01	Pro-Lube-ALK™ Synthetic Compressor Oil	1 Gallon Jug	095247090341	4

Pro-Lube-ALK™ 150