

## Hef-T-Foot™

**Product**  
Hef-T-Foot™

### Features

The Hef-T-Foot™ supports small pipework and runs of cable tray, and can also be used to mount a/c condensing units, air source heat pumps and a variety of outdoor equipment.

### Hef-T-Foot™ with Steel Strut

- Stabilization flange flared out from outer walls
- Domestic - Made in the USA!
- Resistant to impact
- Suitable for drilling for securing equipment

### Hef-T-Foot™ Universal

- Gray
- Injection molded high-impact polypropylene
- Unaffected by UV or weather
- Heavily textured surface for non-skid
- DiversiTech Limited Lifetime Warranty

### Hef-T-Foot™ Installation Kits

Mini-Split outdoor unit installation kit includes 2 Hef-T-Feet and installation hardware to attach an outdoor unit.



**FF-400-S**



**FF-600-S**



**FF-600-S-KIT**

### Materials

Type	Material
<b>Rubber</b>	Compression molded using milled, sieved and graded, recycled rubber bound with high quality adhesive. Density 1.0g/cm <sup>3</sup> . Working temperature range -10°C to 75°C (14°F to 167°F).
<b>Strut</b>	41mm x 21mm x 1.5mm (1.6" x .83" x .06") galvanised steel
<b>Inserts</b>	M10 (metric course thread) x 20mm/.79", zinc plated steel, through inserts. Maximum torque 15Nm. Maximum load 25kg/55lbs.

### Hef-T-Foot™ with Steel Strut Product Specifications

Item No.	Description	Length	Width	Height	Weight	Max. Load
<b>FF-250-S</b>	Hef-T-Foot™ 250mm/9.84" Strut	250mm/9.84"	185mm/7.28"	100mm/3.94"	2.8kg/6.2lbs	125mm/275lbs
<b>FF-400-S</b>	Hef-T-Foot™ 400mm/15.75" Strut	400mm/15.75"	185mm/7.28"	100mm/3.94"	4.6kg/10.1lbs	200mm/440lbs
<b>FF-600-S</b>	Hef-T-Foot™ 600mm/23.62" Strut	600mm/23.62"	185mm/7.28"	100mm/3.94"	7.6kg/16.7lbs	300mm/660lbs
<b>FF-1000-S</b>	Hef-T-Foot™ 1000mm/39.37" Strut	1000mm/39.37"	185mm/7.28"	100mm/3.94"	12kg/26.4lbs	500mm/1100lbs

### Hef-T-Foot™ Universal Product Specifications

Item No.	Description	Length	Width	Height	Weight	Max. Load
<b>FF-250-UNI</b>	Hef-T-Foot™ 250mm/9.84" Universal	250mm/9.84"	185mm/7.28"	100mm/3.94"	2.8kg/6.2lbs	125mm/275lbs

### Hef-T-Foot™ Installation Kit Product Specifications

Item No.	Description	Max. Load
<b>FF-400-S-KIT</b>	1 Pair of FF-400-S + Installation Hardware	400kg/880lbs per Pair
<b>FF-600-S-KIT</b>	1 Pair of FF-600-S + Installation Hardware	600kg/1320lbs per Pair
<b>FF-1000-S-KIT</b>	1 Pair of FF-1000-S + Installation Hardware	1000kg/2200lbs per Pair